



OIL PRIMER

PRODUCT DESCRIPTION	Duralex Oil Primer is a high-quality solvent-based primer. It is designed to reduce damages produced by alkali and salts in new or old masonry surfaces. It seals porous and powdery surfaces to facilitate the application of Top Coats.				
INTENDED USES	Duralex Oil Primer is recommended for all interior & exterior brickwork, concrete, masonry, cement rendering and wall boards.				
FEATURES	• Good sealing property • Resistant to mild chemical fumes attack. • Facilitate stronger adhesion of top coat • High Coverage				
PRODUCT INFORMATION	Appearance	Matt			
	Colour	White			
	Binder Type	Alkyd			
	Pigment Type	Light Fast Non-Lead Pigments			
	Solvent	Naphtha Petroleum			
	Application	Brush, Roller and Spray			
	Flash Point	35°C			
	Cleaning	Clean all equipment with Duralex Universal Thinner immediately after use			
	Thinner	Duralex Universal Thinner			
	Thinning	20 – 25 %			
	Coverage	12 - 14 m ² / Liter / coat Actual Spreading rate depends on film thickness, surface porosity, imperfections, temperature or wastage.			
	Specific Gravity	1.57 ± 0.02			
	Volume Solids (Theoretical)	48 ± 2%			
	No. of Coats	1			
	Wet Film Thickness	70-80 µm / liter / coat			
Dry Film Thickness	35-40 µm / liter / coat				
Packing	3.64, 4, 14.56 and 20 liter				
Drying Information		5°C	15°C	25°C	35°C
Touch Dry		04 hrs	03 hrs	02 hrs	01 hr
Hard Dry		16 hrs	14 hrs	12 hrs	08 hrs
Recoat		16 hrs	14 hrs	12 hrs	08 hrs
Drying and recoat times are temperature, humidity and film thickness dependent.					
SURFACE PREPARATION AND APPLICATION		Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below. New or Bare Surfaces: New concrete, mortar or cement render must be allowed to cure for 8-12 weeks depending on concrete thickness and drying condition. Surface to be painted must be dry clean and free from all contamination and efflorescent salts. Remove dirt, grease and waxy material by rubbing down using a suitable sand paper. Apply one coat of Duralex Oil Primer and allow the surface to dry out completely, scuff the surface with suitable sand paper and dust off.			

Previously Painted Sound Surfaces: Scrap off all the loosely adherent and defective paint from the surface with an appropriate abrasive paper or stiff brush and dust off. Spot prime with Durallex Oil Primer and allow the surface to dry out completely. Scuff with a suitable sand paper and dust off.

Finishing: After surface preparation apply 2-3 coats of Durallex top coat. Ensure complete drying between successive coats. Thinning ratio must be followed for application procedure.

Stir thoroughly before use

RECOMMENDED PAINT SYSTEM

Sequence	Products	No. of coats
Primer	Durallex Oil Primer	01
Finish	Recommended Top Coat	2-3

Consult Durallex Paints representative for the system best suited for the surfaces to be painted

HEALTH & SAFETY

- Must use goggles, gloves at the time of application.
- A suitable dust mask must be worn when rubbing down.
- Do not smoke while applying paint.
- Keep doors and windows fully open to ensure proper ventilation when applying paint.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of contact with skin, remove splashes from skin using soap and water.
- Don't breathe spray mist or dust.
- Swallowing can result in nausea, vomiting and irritation of gastrointestinal tract.
- This container is only for paint use. Don't use it for edible storage.
- In the event of an accident, collect spillage using sand or earth.
- Do not empty into drains or watercourses.
- Toxic to aquatic environment.
- Toxic by inhalation. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, seek medical advice and show container label.
- Keep out of the reach of children.
- Protect from extremes of temperature. Store in a cool and dry place.
- Safety data sheet available for professional users on request.

NOTE

WARNING: Scrapping/sanding off previously painted surfaces may release hazardous fumes which is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.

The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given is subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.

The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However, results may vary due to possible variations in field conditions and application procedures.

UNIVERSAL Paint Industries
Rajbah Road, Link Sumandri Road, Faisalabad 38050, Pakistan
Phone: +92-41 00000000, +92-300-0000000
info@duralexpaint.com, www.duralexpaint.com UAN: +92-41 000-00-0000