



# PREMIUM CLEAR VARNISH

**PRODUCT DESCRIPTION** Duralex Premium Clear Varnish is a solvent-based varnish having superb gloss and excellent abrasion resistance.

**INTENDED USES** It is suitable for all types of interior and exterior wood, cane, wall paneling and metal surfaces.

- FEATURES**
- High gloss and durable
  - Resistant to the levels of atmospheric humidity present in normal interior and exterior environment.
  - Resistant to mild chemical fumes attack

|                            |                                    |                                                                                                           |
|----------------------------|------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>PRODUCT INFORMATION</b> | <b>Appearance</b>                  | Gloss                                                                                                     |
|                            | <b>Color</b>                       | Transparent                                                                                               |
|                            | <b>Binder Type</b>                 | Alkyd                                                                                                     |
|                            | <b>Pigment Type</b>                | N/A                                                                                                       |
|                            | <b>Solvent</b>                     | Naphtha Petroleum                                                                                         |
|                            | <b>Application</b>                 | Brush, Roller and Spray                                                                                   |
|                            | <b>Flash Point</b>                 | 34°C                                                                                                      |
|                            | <b>Cleaning</b>                    | Clean all equipment with Duralex Universal Thinner immediately after use                                  |
|                            | <b>Thinner</b>                     | Duralex Universal Thinner                                                                                 |
|                            | <b>Thinning</b>                    | 10 – 15 %                                                                                                 |
|                            | <b>Coverage</b>                    | 11-13 m <sup>2</sup> / Liter / coat                                                                       |
|                            |                                    | Actual Spreading rate depends on film thickness, surface porosity, imperfections, temperature or wastage. |
|                            | <b>Specific Gravity</b>            | 1.08 ± 0.02                                                                                               |
|                            | <b>Volume Solids (Theoretical)</b> | 45 ± 2%                                                                                                   |

|                           |                         |
|---------------------------|-------------------------|
| <b>No. of Coats</b>       | 2-3                     |
| <b>Wet Film Thickness</b> | 75-90 µm / liter / coat |
| <b>Dry Film Thickness</b> | 35-40 µm / liter /coat  |
| <b>Packing</b>            | 1 and 4 Liters          |

| Drying Information | 5°C    | 15°C   | 25°C   | 35°C   |
|--------------------|--------|--------|--------|--------|
| Touch Dry          | 06 hrs | 04 hrs | 03 hrs | 02 hr  |
| Hard Dry           | 24 hrs | 20 hrs | 16 hrs | 12 hrs |
| Recoat             | 24 hrs | 20 hrs | 16 hrs | 12 hrs |

Drying and recoat times are temperature, humidity and film thickness dependent

**SURFACE PREPARATION AND APPLICATION** Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below.

**New or Bare Surfaces:** Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff the surface along the grains of the wood with suitable sand paper and dust off.

# PREMIUM CLEAR VARNISH

**Previously Painted Sound Surfaces:** Previously painted sound surfaces should be thoroughly rubbed down using a suitable abrasive paper and dust off.

**Finishing:** After surface preparation apply 2-3 coats of Duralex Premium Clear Varnish. Ensure complete drying between successive coats. Thinning ratio must be followed for application procedure.

**Stir thoroughly before use**

Consult Duralex Paints representative for the system best suited for the surfaces to be painted.

---

## HEALTH & SAFETY

- Must use goggles, gloves at the time of application.
  - A suitable dust mask must be worn when rubbing down.
  - Do not smoke while applying paint.
  - Keep doors and windows fully open to ensure proper ventilation when applying paint.
  - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
  - In case of contact with skin, remove splashes from skin using soap and water.
  - Don't breathe spray mist or dust.
  - Swallowing can result in nausea vomiting and irritation of gastrointestinal tract.
  - This container is only for paint use. Don't use it for edible storage.
  - In the event of an accident, collect spillage using sand or earth.
  - Do not empty into drains or watercourses.
  - Toxic to aquatic environment.
  - Toxic by inhalation. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, seek medical advice and show container label
  - Keep out of the reach of children.
  - Protect from extremes of temperature. Store in a cool and dry place.
  - Safety data sheet available for professional users on request.
- 

**WARNING:** Scrapping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.

## NOTE

The information in this data sheet is not intended to be exhaustive; any person using the product for any purpose other than that specifically recommended in this data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at their own risk. All advice given or statements made about the product (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the factors affecting the use and application of the product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability at all for the performance of the product or for (subject to the maximum extent permitted by law) any loss or damage arising out of the use of the product. We hereby disclaim any warranties or representations, express or implied, by operation of law or otherwise, including, without limitation, any implied warranty of merchantability or fitness for a particular purpose. All products supplied and technical advice given is subject to our Conditions of Sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is liable to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to check with their local representative that this data sheet is current prior to using the product.

*The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However, results may vary due to possible variations in field conditions and application procedures.*

UNIVERSAL Paint Industries  
Rajbah Road, Link Sumandri Road, Faisalabad 38050, Pakistan  
Phone: +92-41 00000000, +92-300-0000000  
[info@duralexpaint.com](mailto:info@duralexpaint.com), [www.duralexpaint.com](http://www.duralexpaint.com) UAN: +92-41 000-00-0000